

15" LCD STINGRAY SERIES

U09-T150



slim
model

artistry in technology

Monitor Specifications

U09-T150

Feature	Specification
LCD Panel	15" TFT LCD Active Matrix Display
Resolution	1024 x 768 Pixel, 16.7M Colors
Contrast Ratio	400:1
Brightness	250 cd/m2
Response Time	12 ms
Pixel Pitch	0.297 mm x 0.297 mm
Plug & Play	DDC 2B Compliance
OSD (On Screen Display)	AutoTune, Brightness, Contrast, Clock, Phase, H-position, V-position, Recall
Touch Technology	5 Wire Resistive
Touch Interface	USB or Serial
Touch Active Area	11.95"(303.50 mm) x 8.96"(227.50 mm)
Operating Environment	0°C-40°C (32°F-104°F) 10%-80% (no condensation)
Storage Conditions	-20°C-60°C (-4°F-140°F) 10%-90% (no condensation)
Product Dimension (W/H/D) mm	13.5"(343mm) x 14.3"(363mm) x 7.3"(185mm)
Package Dimension (W/H/D) mm	18.6"(472mm) x 17.5"(444mm) x 8.2"(208mm)
Weight Net / Gross	10 Lbs (4.54 Kg) / 13.9 Lbs (6.3 Kg)
Stand Style	PED-3 Cable Management Base
Mounting Option	Desktop Placement, Bolt Down & VESA Mountable
Monitor Tilting Degree	160 Degree
Color	Black
Viewing Angle	-75°/+75°/-70°/+70°(L/R/U/D)
MTBF	50,000 Hours
PC Video Interface	Analog RGB (VGA)
Horizontal scan rate (KHz)	30 ~ 60 KHz
Vertical scan rate (Hz)	56 ~ 75 KHz
Display Mode	VGA 720x400 (70Hz) VGA 640x480 (60/66/70/72/75 Hz) SVGA 800x600 (60/70/72/75 Hz) XGA 1024 x 768 (56/70/75 Hz)
Front Control	Power On/Off with LED, Menu, AutoTune, Adjustment (+/-)
Built-in Speaker	N/A
Electrical Power	Adapter Input 100-240 VAC,50-60HZ 1.5A Adapter Output 12 VDC, 3.33A (C+)
Power Consumption	30W (Max)
Certification	FCC, CE, MIC, UL

* See Optional Accessories

Specifications subject to change without notice.

Models

Part Number	Description	Type	Interface	Color
U09-T150SR-B	15" LCD	5 Wire Resistive	Serial	Black
U09-T150UR-B	15" LCD	5 Wire Resistive	USB	Black
U09-T150DR-B	15" LCD	5 Wire Resistive	Dual Serial/USB	Black

Optional Accessories

U04-APMB	Pole Mount
U04-AWMA	Short Robotic Wall Arm
P-XM90K	MSR Card Reader, Black, KBW
P-XM90U	MSR Card Reader, Black, USB
US-MSR-BRA	MSR Bracket Kit